



Ageless® GPS Master Oscillator

Model 8194B



- **Reduce HDTV Adjacent Channel Interference**
- **Calibration Labs, Engineering Labs and Factory Reference**
- **GPS Time RAIM Satellite Error Detection**
- **Zero Calibration Costs**
- **5-Year Limited Warranty**

The patented Spectracom Ageless Master Oscillator is a highly accurate frequency and timing source. Outputs are locked to the United States Naval Observatory via the NAVSTAR Global Positioning System (GPS). A Time Receiver Autonomous Integrity Monitor (T-RAIM) algorithm detects and disqualifies faulty satellites to maintain the reliability of system outputs. Spectracom's field-proven Ageless Oscillator technology provides continuous automatic frequency control, compensating for aging and temperature drift.

The Ageless Master Oscillator is ideally suited for use as a site master oscillator for communications systems. Typical applications include calibration, narrow band land mobile radio, paging simulcast, satellite/microwave communication links, and broadcast radio and television. To support your installation, Spectracom offers ancillary system components, including distribution amplifiers, frequency synthesizers, clock selectors, and clock converters.



OUTPUT ACCURACY

locked: $\pm 1 \times 10^{-11}$ typical, 24-hour average
 unlocked: $\pm 2 \times 10^{-9}$ /week typical aging

FRONT PANEL

10 MHz:

One 10 MHz output (BNC Female); 750 mVrms sinewave, 50 ohm impedance
 30 dB harmonic suppression.

1 PPS:

TTL signal (BNC Female), accuracy is ± 500 nanosecond typical with SA off and in position hold.

DATA COMM PORT:

RS-232 (DB 9 Female) interface for maintenance and performance monitoring.

REAR PANEL

10 MHz:

Four 10 MHz outputs (BNC Female); 750 mVrms sinewave, 50 ohm impedance
 30 dB harmonic suppression.

PHASE NOISE AT 10 MHZ OUTPUTS:

Phase Noise:	Offset:
<97 dBc	1 Hz
<110 dBc	10 Hz
<125 dBc	100 Hz
<135 dBc	1000 Hz

DATA CLOCK OUTPUTS:

Disciplined 1 PPS at RS-485 levels (DB 9 Female)

ALARM OUTPUTS:

Relay contacts SPDT, 2A @ 30 VDC (terminal strip)

GPS ANTENNA:

L1, C/A Code transmitted at 1575.42 MHz ("N" Type Female)

Received Frequency: 1575.42 MHz

Satellites Tracked: Up to 12, simultaneous, GPS TRAIM satellite error management

POWER:

115/230 VAC $\pm 15\%$, 50/60 Hz (3-prong connector, 7' cord included).
 Maximum power consumption, 20W. *Option 03* adds 25W.

OPTIONS

INTERNAL FREQUENCY DISTRIBUTION AMPLIFIER:

Option 03 converts four 10 MHz outputs to an output amplifier to the equivalent of *Model 8140*. Provides 10 MHz and +12 VDC to power LineTaps, MultiTaps, and VersaTaps which can also provide frequencies other than 10 MHz. For more information, see *Model 8140* data sheet.

FREQUENCY OUTPUTS:

Option 07 converts four 10 MHz rear panel outputs and the front panel output to 5 MHz.

MOUNTING SLIDES:

Option 11 provides mounting slides to enable rack mounting in a 19" rack with slide-out capabilities.

POWER:

12 VDC; *Option 52*, ± 13.8 VDC $\pm 20\%$ (terminal strip)
 24 VDC; *Option 53*, ± 27.6 VDC $\pm 20\%$ (terminal strip)
 48 VDC; *Option 54*, ± 55.2 VDC $\pm 20\%$ (terminal strip)

PHYSICAL & ENVIRONMENTAL

SIZE/WEIGHT:

EIA 19" W X 3.5" H (2ru) x 12.5" D/16 lbs. maximum

INDICATORS:

Power, tracking GPS, oscillator locked, minor alarm, major alarm

ENVIRONMENTAL:

-30° to +60° C (-22° to +140° F) operating range
 -40° to +85° C (-40° to +185° F) storage range
 95% R.H. non-condensing

FCC INFORMATION

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

ORDERING INFORMATION

- Specify *Spectracom Model 8194B*, plus:
Option 03: Internal Frequency Distribution Amplifier
Option 07: 5 MHz Outputs
Option 11: Mounting Slides

For power input other than 115/230 VAC:

Option 52: 12 VDC
Option 53: 24 VDC
Option 54: 48 VDC

- Specify *Antenna and Accessories*:
 GPS Outdoor Antenna, *Model 8225* and mounting hardware
 Antenna Preamplifier, *Model 8227*
 Antenna Surge Protector, GPS, *Model 8226*
 Antenna Flat Roof Mount, *Model 8213*
 Antenna Cable, LMR-400 equivalent, CAL7xxx (xxx=length in feet)

WARRANTY

5-Year Limited Warranty